

Epoxy HB Coating

Resfloor Epoxy High Build Coating is a 100% solids, solvent free 2 part epoxy resin floor coating.

Applied at a thickness of around 0.6mm over two coats, the finish provides a smooth, sealed and gloss coloured coating.

- **Apply by Brush, Roller or Squeegee**
- **Ideal For: Light Industrial, Storage & Workshops**
- **Solvent free low odour formulation**
- **Produces sealed easy to clean finish**
- **Slip Resistance additive available**
- **High Build Gloss finish**



Typical Uses

For medium duty areas requiring an easy to clean, tough and durable coating with excellent chemical resistance such as warehouses, factories, workshops, showrooms, packing and storage areas.

Curing Period	10°C	20°C	30°C	Consumption over 2 coats	
Light Traffic	48 hrs	16 hrs	12 hrs	Unit Size	5 kg
Full Traffic	72 hrs	48 hrs	40 hrs	Over 100m ²	0.5 kg/m ²
Full Cure	12 days	7 days	5 days	Less than 100m ²	0.55 kg/m ²
Pot life	30-40 mins	15-20 mins	5-10 mins	Less than 50m ²	0.6 kg/m ²

Standard Colours

Light Grey



Mid Grey



RAL Colours*

RAL 6002




RAL 3020



RAL 5017



RAL 9011



RAL 1032



RAL 9003



*please note that RAL colours are different cost to standard colours

Please also read the following documents before application:

For detailed instructional guidance see our Installation Guide.

For full technical data see our Technical Data Sheet.

For material safety see our SDS documents.